

# In-Ground Swing Gate Openers

## Kit Ref: SP-DU.3R

Suitable For Domestic Use



### ITEMS INCLUDED IN STANDARD APPLICATION KITS

- DU.IT14N Operator(s) (230v ac)
- DU.CZS Galvanised Foundation Boxes (110°)
- DA.HEAD Panel (Built In Receiver)
- Two T2WV Transmitters
- Pair of Pupilla Photocells
- Aerial



## Kit Ref: SP-DU.4C

Suitable For Intensive Use



### ITEMS INCLUDED IN STANDARD APPLICATION KITS

- DU.350VN Operator(s) (230v ac)
- DU.110 Galvanised Foundation Boxes (110°)
- DA.HEAD Panel (Built In Receiver)
- Two T2WV Transmitters
- Pair of Pupilla Photocells
- Aerial



A device is available for the DU.IT14 or DU.350 operators to enable the opening angle to be extended to 180°

# In Ground Swing Gate Kits

Description	Opening Time to 90°	Single Kit code	Double Kit Code
<b>DU.IT14 DOMESTIC USE</b> c/w galvanised steel foundation box & DA. BRAIN multifunction control panel. Suitable for 3m leaf, max weight 500kg, 110° standard opening.	20 seconds	DU.3R/1	DU.3R
<b>DU.350 INTENSIVE USE</b> c/w galvanised steel foundation box & DA. BRAIN multifunction control panel. Suitable for 4m leaf, max weight 500kg, 110° standard opening.	18 seconds	DU.3C/1	DU.3C
<b>DU.350VN INTENSIVE USE Fast version</b> c/w galvanised steel foundation box & DA. BRAIN multifunction control panel. Suitable for 3m leaf, max weight 500kg, 110° standard opening.	11 seconds	DU.4C/1	DU.4C



**Product Ref: 97-K42**  
**Coded Keypad**



**Product Ref: 97-CCL-A1**  
**1 Call Button**  
**Audio Intercom System (100m)**  
If required, an enclosure for the transformer is available



**Product Ref: 97-CCL-VI**  
**Black & White Anti Vandal**  
**Video Intercom System (100m)**



**97-WI**  
**Wireless Intercom Kit**

**97-WI-KEY**  
**Wireless Intercom Kit & Keypad**

Please consult our sales department for all available access control options